
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

T.1N., R.26E., INDEX A-3

History of original corner establishment:

Survey General notes state: under G.L.O. contract number 99, dated July 8, 1861. This corner was originally established by Ebenezer E. Haft

and raised a mound with trench and pits as per Deposited a pint of charcoal set a post for qr sec corner instructions.



Description of corner evidence found:

corner positions, accepted this position as the best available evidence. Found remains of a north and east fence corner. Due to its near record relationship to surrounding accepted

original location of this corner: Description of monument and accessories I establish to perpetuate the

shown in the DIAGRAM, 28" in the ground. At the above said fence corner position, set a 2-1/2"dia.x 30" aluminum pipe w/3"dia. aluminum cap, stamped as

From which;

A 5/8"x 30" rebar pin bears N45°W 9.9 ft. is set 30" deep, no marks on top of pin.

A 5/8"x 30" rebar pin bears N45°E 9.3 ft. is set 30" deep, filed 1 groove on top of pin.

A 5/8"x 30" rebar pin bears S45°E 9.5 ft. Top is 1 foot below ground, filed 2 grooves on top of pin.

A 5/8"x 30" rebar pin bears S45°W 9.8 ft. Top is set 1 foot below ground, filed an X on top of pin.

DIAGRAM T2N R26E 1/4 --2003 PLS49865 **S31** TIN 86

Measurements to accessories taken with a magnetic compass, declination 17°-30' East, and distances measured with nylon clad steel tape. Placed yellow plastic caps stamped "FS&E Survey Marker" on all rebar pin accessories.

as shown hereon on February 20, 2003 I hereby certify that the above corner point was perpetuated

	Witness:
Bradley R. Cates, LSIT	D. Mitchell Ferguson, LSIT

County Chang	-	for record on the	State of	Office of
ACCIONAL.			State of Oregon	County
		day of		Office of County Surveyor
Denuty	by		ertify that the	County of
		2003	within instrument w	County of Morrow
			. I hereby certify that the within instrument was filed in this office	

RENEWAL

DATE 12/31/2003