CERTIFIED RECORD OF LAND CORNER MONUMENTATION

T.1N., R.26E., INDEX A-3

History	٥f	original	corner	establishme	nt:
TITISTATA	UΙ	ULIZILIAI	COLUCI	CSCADIISIIIIIC	<i></i>

This corner was originally established by Ebenezer E. Haft under G.L.O. contract number 99, dated July 8, 1861. Survey General notes state:

Deposited a pint of charcoal set a post for qr sec corner and raised a mound with trench and pits as per instructions.

	Se					
	•					

Description of corner evidence found:

Found remains of a north and east fence corner. Due to its near record relationship to surrounding accepted corner positions, accepted this position as the best available evidence.

Description of monument and accessories I establish to perpetuate the original location of this corner:

At the above said fence corner position, set a 2-1/2"dia.x 30" aluminum pipe w/3"dia. aluminum cap, stamped as shown in the DIAGRAM, 28" in the ground. From which;

A 5/8"x 30" rebar pin bears N45°W 9.9 ft. is set 30" deep, no marks on top of pin.

A 5/8"x 30" rebar pin bears N45°E 9.3 ft. is set 30" deep, filed 1 groove on top of pin.

A 5/8"x 30" rebar pin bears S45°E 9.5 ft. Top is 1 foot below ground, filed 2 grooves on top of pin.

A 5/8"x 30" rebar pin bears S45°W 9.8 ft. Top is set 1 foot below ground, filed an X on top of pin.


<u>DIAGRAM</u>
T2N R26E
S31
1/4
S 6
T1N
2003
PLS49865

Measurements to accessories taken with a magnetic compass, declination 17°-30' East, and distances measured with nylon clad steel tape. Placed yellow plastic caps stamped "FS&E Survey Marker" on all rebar pin accessories.

I hereby certify that the above corner point was perpetuated as shown hereon on February 20, 2003

Witness:

D. Mitchell Ferguson, LSIT Bradley R. Cates, LSIT



RENEWS: 1/1/2004

Office of	County	Surveyor	County of	<u> Morrow</u>	
				within instrument was	filed in this office
for record	l on the <u>4</u>	th day of _	March	, 2003 - 2014	
Styl	Ruk. H	adock	by		
County Si	irveyor		Deputy		