# History of original comer establishment:

Everett The original corner Thatcher as was follows: established in 1879 by

Α

From stone which: 10"x10"x6" for corner to sections 24, 25, 19, and

Tamarack, 8" 6" 11 diameter bears N41° N<sub>5</sub> ರೈ. Ç lks. distance

Black black pine, pine, 6" in Pine, 7" in 'n diameter diameter bears bears bears ຜ່ໝ 60°E 79 o` W Q 17 lks. lks. distance. dist æ

### ほらりほ DIAGRAM S24 S25 TSS R-25 S19 728

## Description of corner evidence found:

Original bearing tree, with visible scribes "with visible scribes", "" winck pine, S79°W, There are obvious errors in the G.L.O. rec therefore determine the scribed blaze on record distance for the S.W. B.T., I set of this tree. A down and decayed lodgepole pine with scribes double unhealed blazes bears N60°E, 10.0 ft. This tree has re cannot determine bearing C no trees to the N.E. scribing, the west and the tree, a 14" western larch snag welbes "R27E S30", and lower healed 79°W, 11.2 ft). A 14" western lang, and healed lower blaze bears its original perrors in the 14" fence have B.T., I ice which position. been destroyed s h record a point 0.5 ft Record western ъу This tree has rolled larch with East. tree the clearing North, which is in harmony with the pine blaze, larch for accessories , 18.0 ft " previously gpened e, bears S79 E, ll From this point, section for snag "E S19 BT" fence faces for 19 There downhill this ned upper 11.2 ft. N79°W and using opened upper original ís no visible corner record blaze (Record on

### original location of this corner: Description of monument and accessories I established to perpetuate the

213" F cap brass marked: attached, 29" determined above, into the ground and H set set a 2"x32" galvanized iron raised mound of stone aroun 2"x32" around pipe, pipe. T5S with Brass

### From which:

> 91 9" white α single blaze, bears s73°30'W, 14.2 rt rt scribed "T5S R26E **S25** BT"

因の22 日

S24 S25

H 72 R

PLS 16 1983

1636 S19 S30

A 8" white fir bears N290W, 29.1 ft scribed "T5S R26E S24 BT"

92 Ø single

bears N46°30'E, 19.0 iri rt scribed "T5S R2 7E S19 BT"

on a single western single blaze, n larch blaze. bears S67030'E, 19.3 Hr ct • scribed "T5S R27E S30 BT"

54-3 and 54-4 signs were placed on bearing trees

Compas Declination 20<sup>0</sup>€

on ₩ŧ hereby September certify 28 the 1 above corner location was perpetuated ន្ឋ hereon described

Witness: Susan H Newstett

on the..... Oregon COURTY SHEVEYOR ..... County of ......MARION .... (COUNTY OFFICIAL) of..... I hereby certify that the within instrument was filed in this (DEPUTY) ×-4 offic PROF DENNIS L. REGISTERED SURVEYOR = GAYLORD 0

Form R6-7100-57 (9/71)

State of ....

RECLIVED

Morrow County Surveyor

Rec'd Date NL

E Y