CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Index: 2-15

Center south 1/16 corner section 3, T.5S., R.26E., W.M.

Corner first set by PLS 1638in 1975.
His record reads: Set a 2 1/2" x 30" iron pipe 28" in the ground, with a brass cap marked as shown. (see diagram). From which I scribed BT's:
A lodge pine 10" in diam. bears N02°E 14.5' marked CS 1/16 SS BT.
A lodge pine 12" in diam. bears S81°W 13.9' marked CS 1/16 SS BT.

DIAGRAM

T5S R26E
3
S1/16 1 SS
S
1975
PLS 1638

Description of corner evidence found:
Found the iron pipe as described with brass cap stamped as shown in the diagram. From which:
A dead and down 9" dbh Ponderosa Pine bears N0°00'W. 14.4' with visible scribe.
A dead and down 11" dbh Ponderosa Pine bears S58°18'W. 14.2' with visible scribe.

Description of monument and accessories I established to perpetuate the original location of this corner:
The bearings were based on the surveyed bearing between the 1/4 witness corner and the N 1/16 corner of sections 3 and 4 as recorded by PLS 1638 in Morrow County survey 286-K. I set the following new witness trees:
A 11" dbh Engelman Spruce bears S82°13'W, 30.8' scribed CS1/16SSBT;
A 21" dbh Western Larch bears N73°41'E, 30.8' scribed CS1/16SSBT;
An aluminum washer stamped PLS 852 is nailed between the letters B and T on the new trees. All the BT's have LSM and BT signs attached.
Painted 6" red bands around all the trees and painted the scribe blazes red.

This work was done October 29, 1992.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

David L. Haddock

OREGON
JULY 12, 1968
DAVID L. HADDOCK
852

Office of _____ County of _____
State of _____, I hereby certify that the within instrument was filed in this office for record on the _____ day of _____, 19____.
_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

Form 6L-7100-27 (9/71)