CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No.E-23

History of original corner establishment:

The original Sanderson und September 7, under G.L.O. contract 368, 7, 1880. His record reads: by Ed , dated

បួមនា Set Stone cor. 14x12x6 in stone mound for

> DIAGRAM T68 \$1 1/4---S12 PLS 8 .S 852 1987 R26E

Description of corner evidence found:

Another Found 14x12x6 punom. stone 60' to ď with the east 1/4 marked on had no n face marked stones small stone mound.

Description of monument and accessories I established to perpetuate the

original location of this corner:
Set a 2" I.D. galvanized iron pipe 30" long
26" into the ground and stamped the cap as
Buried the original stone along side the mo 30" long monument. g with shown in 1/2" diagram bras above cap

steel f Survey Placed Monument a Ωi diameter post 5' w and Property collar west of west of s Boundary stone around monument signs th Forest attached. the orest Serv and vice set . Land

Set Marked 1/2" the caps 2411 rebar 3 25 shown with below: 2" aluminum caps for bearing objects.

1/4 COR S 2 852 в. 0

COR $\mathbf{S}_{\mathbf{I}}$ 852 112 20.0. Ø REGISTERED PROFESSIONAL LAND SURVEYOR

certify hereon the above described on August corner point ţţ, was was perpetuated 1987.

a H

David L. Haddor

September 19

DAVID OREGON
JULY 12, 1968
D L. HADDOCK
852 ω. σ.

for record on the 19 day of DECEMBER. State of COUNTY Office of. COUNTY OFFICIAL) SURVEYOR . , I hereby certify that the within instrument was filed in this office ... County of 19.26 MORRON (DEPUTY)