History of original corner establishment:

This corner Sanderson, u r was o establis r General shed La ed in า 1880 Offic င ၉ တ 2,0 / Edward

Surveyor General S records S ct Ø te

Set: stone 12" > ter corner: 12" × 12" > × which: .10 ⊐. ⊐ ω S tone mound fo

М. No.368. /4 DIAGRAM **T6S =** S31 T7S R26E

P ne ne 9=6= dia. Ω, bears bears North __ __ __ __ 00 links East 0 4 ----

픘

Description of corner evidence found:

found irmly നവ ct : 0 tone No 12" x 1: evidence ന ഗാ = x 10" remains S mark the e o i th n 1/4 iýgnal on the Nort I bearing tr it h e s a C

original location of this corner: Description of monument and accessories I established to perpetuate

I set : 12" in α <u>=</u> mound 30 = 0 f flanged stone, marked: ъe ¥. ťh S) 2 1/2" 7 S S Ġ, . 7 Sodx ed

I place the ori and take the formeasurements to blaze in which LS 1679: original stone alongside a following bearing trees, to the center of the tree ich I place a brass washer as a men , and tal ee at the r stampee memorial take the lower lower

1/4 91 S S 1980 **S3** R26 7S 79

0 mkd. 11" dia. d 1/4 S31 6" dia. ! bears BT North Q -1/2 ည လ 4 \sim \sim 4> ~₩ e e 4

=== -77 bears S outh g ∞ __ 1/2 SPO ct 21. _ **-**h е е c† mkd 1/4 SS 3

hereby erein da n i o certify scribed the on November orner monument 6, 1980. Ξ ς. S ٦, 0 established as

Witness ВоБ Malott

Var 190 m S

REGISTERED PROFESSIONAL LAND SURVEYOR E G O N Y 14, 1978 C. WEAVER 1679

for regard on the 1.50 State of.... Office of... Oregon Surveyor hereby certify that the within instrument was filed in this office January County of 19.61 Morrow (DEPUTY)

Form R6-7100-57 (9/71)

MOTTON RECLIVED BY August 7 County Surveyo 1881

Rec'd By_ Ref. army, no. C-435-K