CERTIFIED RECORD OF LAND CORNER MONUMENTATION

A-9

History of original corner establishment:

This corner was established in 1879 by A. York under G.L.O. contract No. 309. He set a stone 14"x14"x6" in a stone mound. He called a stream 25 links West of the corner.
This corner was found by E.W. Sanderson in 1881 during his retracement under G.L.O. contract No. 368. He found a stone 19"x12"x7" in a stone mound. He did not call the stream.

DIAGRAM

T6S	R25E
S5	S4
T7S	R25E

Description of corner evidence found:

I found a stone 14"x13"x5" in a stone mound with no marks evident on the stone. Creek is 26' West.

Description of monument and accessories I established to perpetuate the original location of this corner:

I set a 2½"x30" alum, pipe in a stone mound with a 3" alum. cap containing a magnet and marked:
I buried the original stone alongside.
From the corner:
White Fir, 10" dia., bears S16½°W, 15.9 ft.
White Fir, 10" dia., bears S63 3/4°E, 43.9 ft.

The B.T.'s have an "attention" sign, a B.T. tag, a 6" red enamel stripe and an alum. 'PLS 1832" washer and are scribed according to the manual.

There is a 6' steel fence post with an "attention" sign within 5' of the corner.

PLS 1832
T6S R25E
S5 S4
T7S R25E
1984

REGISTERED
PROFESSIONAL
LAND SURVEYOR
Fayette S. Munro
OREGON
JULY 13, 1979
FAYETTE S. MUNRO
1832

RECEIVED BY
Morrow County Surveyor
10/24/84
MLO
697-K

Office of Surveyor County of Morrow
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 2 day of July, 1984
David H. Klein by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

GPO—798-276