


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

A-19

History of original corner establishment:

Aaron F. York, under G.L.O. contract number 309, dated Nov. 18, 1878, surveyed the north line of T7S, R26E. He set a stone 31"X19"X7" and raised a stone mound at the corner.

Edward W. Sanderson, under G.L.O. contract number 368, dated Sep. 7, 1880 retraced York's line and at this corner found a stone 24"X18"X14" in a stone mound.



Description of corner evidence found:

I found a stone 28"X15"X7", with no marks visible, in a mound of stone.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the original corner point I set a 2 1/2"X30" alum. pipe with a 3" alum. cap containing a magnet and marked:

T6S R26E
1/4 S2
T7S R26E
PLS 1832
1985

I buried the original stone alongside and built a stone mound around the monument.

From the corner:

A Juniper, 9" dia., S86 1/2° E, 89.5 ft.; marked: 1/4 S2 BT  
A Juniper, 8" dia., S52 1/2° E, 114.3 ft.; marked: 1/4 S2 BT

BTs have blaze and a 6" stripe painted red, a BT tag, an "Attention" sign and an alum. "PLS 1832" washer nailed to the bottom of the blaze. There is a 6' steel fence post with an "Attention" sign within 5' of the corner.

Measured to center of BTs using steel tape and staff compass. Magnetic declination set at 18 1/2° E.

July 26, 1985

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Fayette S. Munro*

OREGON  
JULY 13, 1979  
FAYETTE S. MUNRO  
1832

Office of Surveyor ..... County of Morrow .....

State of Oregon ..... I hereby certify that the within instrument was filed in this office  
for record on the 24 day of December, 1985

David A. K... by ..... (COUNTY OFFICIAL)

..... (DEPUTY)