

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


A-5

History of original corner establishment:

This corner was established in 1878 by Aaron F. York under General Land Office Contract No. 309.

Surveyor General's records state:

Set stone 14" x 14" x 6" for corner to Sections 5, 6, 31 and 32 and raised mound of stone.




Description of corner evidence found:

Found a stone 14" x 12" x 6" with 5 notches on the East and 1 notch on the West, firmly set in a mound of stone. P. Pine 17" dia. with scribe marks visible in open upper face bears South 68° East, 6.1 feet (not of record).

Description of monument and accessories I established to perpetuate the original location of this corner:

At the exact location of the found stone I set a 2" x 30" flanged G.I. Pipe with a 2-1/2" brass cap marked:



I deposit the original stone alongside as a memorial and take the following trees and take the measurement to the center of the tree at the lower blaze in which I place a brass washer stamped LS 1679:

- D. Fir 9" dia. bears West 7.5 feet mkd. T7S R26E S6 BT.
- D. Fir 11" dia. bears North 51-1/2° West 38.1 feet mkd. T6S R26E S31 BT.

I hereby certify the about corner monument was re-established as herein described on November 6, 1980.

Witness: Bob Malotte Mag. Var. 19°E

Office of... SURVEYOR..... County of... MORROW.....  
 State of... Oregon..... I hereby certify that the within instrument was filed in this office  
 for record on the 1<sup>st</sup> day of... JANUARY....., 1981.  
*David H. Klein* by..... (DEPUTY)  
 (COUNTY OFFICIAL)

Form R6-7100-57 (9/71)

REGISTERED  
 PROFESSIONAL  
 LAND SURVEYOR

*Kurt C. Weaver*  
 OREGON  
 JULY 14, 1978  
 KURT C. WEAVER  
 1679

RECEIVED BY  
 Morrow County Surveyor  
 Date August 7, 1981  
 Rec'd By M. Hughes  
 No. 484-K  
 Ref. drwg. no. C-435-K