

D-704-K-

SURVEYORS AND

P.O. Box 395 • Boardman, Oregon 97818 (503) 922-3093 • (503) 481-9290

— [] & [] CONSULTANTS, INC.

EARL D. MING P.L.S.
President

Survey for Floyd and Joan Smith NW 1/4, Sec, 21, T5N, R.27 E.W.M. <u>Narrative</u>

This survey was performed at Floyd and Joan Smith's request to check Dennis Edward's survey for Hermiston Electric and a survey by Krumbein Engineering for Floyd and Joan Smith. Their concern was with the location of the corners with respect to their sheds and fence line that was East of the sheds. The fence line was 86.00 feet N 72 41' E of the South-

west corner that Edwards set. We researched the deeds in the area and made ties to the old original concrete monuments from Tamblyn's 1935 Plat of Sec. 21. The deed(s were written from old lot lines from this plat and with present information they do not match the existing fence lines. We find that Dennis Edwards and Krumbein Engineering are within 0.1 to 0.2 feet for Northing and 0.1 to 1.3 feet for Easting with our present information, so there are only small survey errors in the property line locations in this area. The fence lines apparently were placed inerror and do'nt match deed calls. The fence on the centerline of 21st Street is the closest being 4 feet East on the south end of the street and 6.5 feet West on the North end.

We also reset the NE & NW Corners to the parcel described in Book 52 Page 154 and are showing locations of Edwards and Krumbein corners on this Survey Map. Referance material was Stanley Wallulis Aug. 1965 Survey

Morrow Co. #65, which showes he used the old Concrete Mons. Edwards Aug. 1980 Survey, Morrow Co. #383-K. Timberland Mc-Cullough Survey # 646-K. Edwards Survey June 1983 Survey for Hermiston Elec. Krumbein Eng. Survey for Floyd Smith. And

Tamblyns 1935 Plat of Sec. 21.

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON DEC. 14, 1979 EARL D. MING

SURVEYORS AND

P.O. Box 395 • Boardman, Oregon 97818 (503) 922-3093 • (503) 481-9290

CONSULTANTS, INC.

EARL D. MING P.L.S.
President

Survey for Floyd and Joan Smith NW 1/4, Sec. 21, T5N, R.27 E.W.M. Narrative

This survey was performed at Floyd and Joan Smith's request to check Dennis Edward's survey for Hermiston Electric and a survey by Krumbein Engineering for Floyd and Joan Smith. Their concern was with the location of the corners with respect to their sheds and fence line that was East of the sheds. The fence line was 86.00 feet N 72 41' E of the Southwest corner that Edwards set. We researched the deeds in the area and made ties to the old

original concrete monuments from Tamblyn's 1935 Plat of Sec. 21. The deed(s were written from old lot lines from this plat and with present information they do not match the existing fence lines. We find that Dennis Edwards and Krumbein Engineering are within 0.1 to 0.2 feet for Northing and 0.1 to 1.3 feet for Easting with our present information, so there are only small survey errors in the property line locations in this area. The fence lines apparently were placed inerror and do'nt match deed calls. The fence on the centerline of 21st Street is the closest being 4 feet East on the south end of the street and 6.5 feet West on the North end.

We also reset the NE & NW Corners to the parcel described in Book 52 Page 154 and are showing locations of Edwards and Krumbein corners on this Survey Map.

Referance material was Stanley Wallulis Aug. 1965 Survey Morrow Co. #65, which showes he used the old Concrete Mons. Edwards Aug. 1980 Survey, Morrow Co. #3836K. Timberland Mc-Cullough Survey # 646-K. Edwards Survey June 1983 Survey for Hermiston Elec. Krumbein Eng. Survey for Floyd Smith. And

Tamblyns 1935 Plat of Sec. 21.

REGISTERED PROFESSIONAL LAND SURVEYOR

Earl & Fring OREGON DEC. 14, 1979 EARL D. MING