

Ferguson Survey
in Sec. 29, Twp. 1 S, R 27 E, W.M.
Near Heppner, Morrow County, Ore.

Folder 1209, Date 4-25-1955

Book: 2, Page: 32A

Surveyed April 25, 1955

By Verl R. Frole

Reg. Ore. Land Surveyor #183

Jerry Branton, chain

Harold Pointer, chain.

We found an unmarked stone in a fence corner which had been recognized by former surveyors as the East $\frac{1}{4}$ Corner of section 29. Back sighting on the fence line running south from this corner we projected a line North 2640 feet and set a hub. We searched here for the sec. corner common to 20-21-28-29 but no evidence was found. However, near our line we found numerous piles of stones which denoted the location of an old fence line. At 2632 feet, our line crossed a fence corner and rock crib.

From this corner I turned to a bearing of South $89^{\circ}45'$ West. At a distance of 2088.8 feet, we set a hub about 50 feet north of a fence corner. According to mutual agreement between the Ferguson brothers, we ran our line $S. 25^{\circ}08'E$ along a fence line and set a hub at 1515.5 feet. From there we ran on a bearing of $S. 47^{\circ}08'W$, 1597.7 feet and set an iron pipe. At this point I turned to a bearing of due west and we chained a distance of 1347.5 feet, and set a hub.

From here I turned to a bearing of due south and we chained 1571.5 to a fence corner, which apparently is the N.E. corner of the S.W. $\frac{1}{4}$ of the S.W. $\frac{1}{4}$ of Sec. 29, although the distance as computed from the N.E. Corner of Section 29 was about 79.5 feet long.