

Surveyor's Narrative:

The propose of this survey is to do a Boundary Line Adjustment for a pending sale and to survey and monument the individual parcels now comprising the tract described in Book 54. Page 357. Morrow County Deed Records.

In 1971 the Plat of "Rasmussen-Lott Addition" to the city of Heppner was Recorded. This Plat was prepared and Platted by Leland L. Myers LS 699. Although it is not clearly indicated on his Plat, the Northeast Corner, based on shown Bearing and Distances from the Initial Point which was the unmonumented Southwest corner of Lot 14. Block 2. of "Preston Looneys Addition" should be in common with the Southwest corner of Lot 4. Block 2. of "Preston Looneys Addition to Heppiner.

Addition to Heppner.

In 1972 Don Staebler, PE 18408, did a Boundary Survey for Joan Hughs in "Preston Looneys Addition" to the the city of Heppner. He based his Survey on found monuments in "Shipley's and "Riverside Additions" which were Replats of part of "Preston Looneys Addition". He then used those found monuments to compute the location of the West line of Lot 4, Block 2, "Preston Looneys Addition" and monumented his computed location for Southwest corner of Lot 4, Block 2 of "Preston Looneys Addition" along with 3 parcels located within Lots 2, 3 and 4, Block 2 and in a parcel lying South of Lot 4, Block 2 and West of Lots 7 and 14 of Block 2 "Preston Looneys Addition" for Hughs.

I don't know which. Myers or Staebler got their pins in the ground first, both show having set monuments at their locations for the Southwest corner of Lot 4, Block 2, "Preston Looneys Addition", but Staeblers West line overlaps the West line of "Rasmussen-Lott Addition" by 13.1 feet. What is interesting is that neither mentioned the other in their work

In 1973 Hughs brought suit against the principals in the "Rasmussen-Lott Addition" for trespass of waterline placement and construction, based on Staeblers Survey. The court records show no details. The case was dismissed

In 1987 Krumbein LS 933 did a survey for Alderman based on the 1972 Staebler Survey for Hughs and shows as found the monument set by Staebler as the Southwest Corner of Lot 4. Block 2. "Preston Looneys Addition". but does not show the Northeast Corner of "Rasmussen-Lott Addition".

show the Northeast Corner of "Rasmussen-Lott Addition".

In 1995 Edwards LS 951 did a "Lot Line Adjustment" for Patterson which was located in the Northernmost parcel of Staeblers Survey for Hughs. Again Staeblers monuments for Hughs are shown as found and used in Edwards Survey.

In an effort to tie a large part of the Northwest part of Heppner together in order to determine how the various previous Surveys fit together I tied into the Ferguson's (LS 848) Survey for Willow Creek Park District. Morrow County. The City of Heppner and Morrow County Grain Growers. This Survey by Ferguson was done in 1999 and covered a large area between the Heppner Highway and Riverside Avenue. I used Ferguson's Record Bearing between his set monuments along the South side of Riverside Avenue as the Bearing Base of My Survey.

I tied the occupation lines on both sides of Morgan Street and compared them to the 1884 Plat of "Preston Looneys Addition" and found that they were within reasonable agreement with the Plat. Part of Gray's East fence which terminates on Morgan Street in this immediate area I wanted justification in holding it's position because of its good fit with neighboring occupation lines. This fence is too new to consider it as an ancient fence. I talked to Merritt Gray about his knowledge of this fence and its history. He stated that the chain link fence was constructed on the same location as an older fence he had first seen in 1947. After consulting with his neighbor who agreed that this old fence was on the boundary between them he gave his OK to remove part of this fence and replace it with chain link located at the same location of the older fence. This is what Merritt Gray did. This fence and its older extension to the South line up with monuments set by Myers for the "Rammussen-Lott Addition".

replace it with chain link located at the same location of the older fence. This is what Merritt Gray did. This fence and its older extension to the South line up with monuments set by Myers for the "Rasmussen-Lott Addition".

As a check I measured the record distance from Gray's East Fence line across the parcels joining to the East of Gray in order to determine which if either would match existing occupation lines and my Survey. The right angle offset distance from the fence to Staebler's Northwest monument is 185.08 feet, the record is 181.00 feet. The right angle offset distance from the fence to the monument which Staebler shows as the Southwest Corner of Lot 4. Block 2. "Preston Looneys Addition" is 167.08 feet, the record is 165.00 feet. The monument which Myers set at the Northeast Corner of "Rasmussen-Lott Addition" lies 181.66 feet from the fence at a right angle offset, the record is 181.00. Unless Hughs sold 16 feet of the lands Staebler surveyed to the principals of "Rasmussem-Lott Addition", then "Rasmussen-Lott Addition is overlapping into what was then Hughs. The result of this exercise? I didn't resolve who was righter or wronger. I lean towards the occupation lines for my survey.

For the alignment of Morgan Street I used for centerline, the midpoint of the average of the occupation lines on both sides of the street to compute the centerline on the west end of my survey and the monument Ferguson set at the intersection of the North right-of-way line of Morgan Street and the Southerly right-of-way line of Riverside Ave. to compute the center of Morgan Street on the Easterly end. I then used this computed centerline to locate the Morgan Street right-of-ways.

For the North line of Gray's property I used my computed Morgan Street Right-of-way.

Morgan Street right-ot-ways.
For the North line of Gray's property I used my computed Morgan Street Right-of-way.
For the East line of Gray's property I held the chain link and older fence Southerly extension to the monument set by Myers which is 6.01 feet North of Gray's Southeast corner.
For the South line of Gray's property I held the North line of "Rasmussen-Lott Addition" as surveyed by Myers.
I used the Deed records recorded in Book 54. Page 357 (describes the parent tract). Book 72. Page 61 and the description recorded on M-10110 Morrow County Deed Records to survey these tracts shown on this record of

DESCRIPTION FOR NEW TAX LOT # 5701, MAP 28 26 2/0/ ADDITION TO THE CITY OF HEPPNER. OREGON. MARKED WITH A STAR DRILL HOLE AT THE NORTH END OF A CHAIN-LINK FENCE CURB AS LOCATED IN THE SOUTHEAST QUARTER OF SECTION 27, TOWNSHIP 2 SOUTH, RANGE 26 EAST OF THE WILLAMETTE

THENCE SOUTH 89° 40° 11° WEST ALONG THE NORTH LINE OF SAID LOT 6 A DISTANCE OF 111.74 FEET TO A 5/8° X 30° STEEL REBAR WITH A PLASTIC CAP DESCRIPTION: THENCE CONTINUING SOUTH 89° 40° 11° WEST A DISTANCE OF 53.26 FEET TO A 5/8° X 30° STEEL REBAR WITH A PLASTIC CAP STAMPED LS 2850: THENCE SOUTH OI° 37' 03" EAST A DISTANCE OF 264.00 FEET TO A 5/8" X 30"

STEEL REBAR WITH A PLASTIC CAP STAMPED LS 2850: THENCE NORTH 89° 40° 11° EAST A DISTANCE OF 165.00 FEET TO THE EAST LINE OF SAID LOT 6: THENCE NORTH OF 37' 03" WEST ALONG THE SAID EAST LINE OF LOT 6 A DISTANCE

OF 148.24 FEET TO A 5/8" X 30" STEEL REBAR WITH A PLASTIC CAP STAMPED LS THENCE SOUTH 86° 38° 48° WEST A DISTANCE OF 110.91 FEET TO A 5/8° X 30° STEEL REBAR WITH A PLASTIC CAP STAMPED LS 2850:

THENCE NORTH OF 17 38 WEST A DISTANCE OF 47.79 FEET TO A 5/8 X 30 STEEL REBAR STAMPED LS 2850: THENCE SOUTH 89° 40° 11° WEST A DISTANCE OF 3.40 FEET TO A 5/8° X 30° STEEL REBAR STAMPED LS 2850:

THENCE NORTH OO' OB' 58" EAST A DISTANCE OF 73.80 FEET TO THE TRUE POINT OF REGINNING OF THIS DESCRIPTION CONTAINING 0.70 ACRES.

SUBJECT TO A 20 FOOT WIDE INGRESS AND EGRESS EASEMENT DESCRIBED BELOW. BEGINNING AT THE 5/8" X 30" STEEL REBAR WITH A PLASTIC CAP STAMPED LS 2850 AT THE TRUE POINT OF BEGINNING OF THE ABOVE DESCRIBED TRACT: THENCE SOUTH OO' 08' 58' WEST ALONG A PART OF THE EAST LINE OF THE ABOVE DESCRIBED TRACT A DISTANCE OF 73.80 FEET TO A 5/8" X 30" STEEL REBAR WITH A PLASTIC CAP STAMPED LS 2850:

THENCE NORTH 89° 51° 02° WEST A DISTANCE OF 20.00 FEET: THENCE NORTH OO' 08' 58' EAST A DISTANCE OF 73.63 FEET TO THE SOUTH LINE OF

THENCE NORTH 89° 40° 11° EAST ALONG THE SAID SOUTH LINE OF MORGAN STREET TO THE POINT OF BEGGINING.

REGISTERED **PROFESSIONAL** LAND SURVEYOR h Conor OREGON JANUARY 20 1998 JUDSON L. COPPOCK 2850

RECEIVED BY

RENEWAL DATE: DEC. 31 2003

Morrow County Surveyor 120/02

BOUNDARY LINE ADJUSTMENT AND SURVEY FOR: MERRITT GRAY HEPPNER. OR 97836

COPPOCK SURVEYING P.O. BOX 495 HEPPNER, OR. 97836 541-676-8750 Job No. 0500128